



Floodlight MODAN LED 50W

The MODAN floodlights are a choice for a long time. The housing is made of aluminum and tempered glass, which gives a high degree of protection IP65. It has a versatile bracket, thanks to which it can be freely adjusted and mounted. They are perfect for lighting buildings, gates, gardens or facades.

SPECIFICATIONS	EDO777285
Source Type:	Floodlight LED
Application:	inside/outside
Installation:	surface
Adjustable:	yes
Dimensions [mm]:	
- height [mm]:	241.5mm
- width [mm]:	197.5mm
- depth [mm]:	46mm
Colour:	black
Material:	aluminium, glass
Cover colour:	milky
Energy efficiency class [A-G]:	
Cooperation with a dimmer:	no
Sensor:	-
TECHNICAL DATA	
Power in the on-mode P _{on} [W]:	50 W
Standby power P _{sb} /P _{net} [W]:	-
Rated voltage [V]:	220-240 V AC
Rated frequency [Hz]:	50-60 Hz
Color temperature [K]:	4000 K
Light color change:	no
Lighting angle [°]:	110°
Color rendering index CRI:	≥70
Color rendering index R9:	15
Useful luminous flux [lm]:	6850 lm
Light distribution angle [°]:	wide cone (120°)
Luminous efficiency [lm/W]:	161,66 lm/W
Rated life [h]:	25000 h
Number of cycles on/off:	15000
On-mode energy consumption [kWh/1000h]:	50kWh/1000h
IP:	IP65
IK:	IK06
Klasa ochronności:	I
Mercury content:	no
Environmental conditions:	-20°C...40°C
LOGISTIC DATA	
Collective packaging [pc.]:	10pc.
Weight [g]:	914g
EAN:	

