## UMA Sand Light Grey




EDO777541



## The hermetic luminaire UMA Sand Light Grey

The hermetic UMA idealie luminaire will prove itself where we want a ceiling luminaire that will be more resistant to mechanical damage and dirt. Thanks to its versatility, the round, simple shape will work well in various rooms. It is available in three different colors.

| SPECIFICATIONS  | ED0777541                      |
|---|--------------------------------|
| Application:  | inside                         |
| Type of assembly:                                     | surface-mounted                |
| Instillation site:                                    | ceiling                        |
| Connection type:                                      | screw cube                     |
| Colour:   | light gray                     |
| Type of finish:                                       | sandblasted                    |
| Material:   | cover-aluminium, shutter-glass |
| Dimensions:   | ø90mm                          |
| -width [mm]:  | -                              |
| -length [mm]:   | ø55mm                          |
| -ring diameter [mm]:                                  | 68mm                           |
| -height [mm]:   | -                              |
| -mounting bolt distance [mm]:                         | no                             |
| Adjustable:   | -                              |
| Shutter:  | yes                            |
| Socket included:                                      | GX53                           |
| Socket type:  | 1                              |
| Number of slots:                                      | no                             |
| Light source included:                                |                                |
| TECHNICAL DATA  |                                |
| Maximum power [w]:                                    | 15W                            |
| Rated voltage [v]:                                    | 220-240 V                      |
| Rated frequency [Hz]:                                 | 50-60 Hz                       |
| IP:   | IP54                           |
| Protection class:                                     | 1                              |
| Mercury content:                                      | no                             |
| Environmental conditions [°c]:                        | -3050°C                        |
| The minimum distance from the illuminated object [m]: | 0,5m                           |
| LOGISTIC DATA   |                                |
| Collective packaging [pcs.]:                          | 40pcs.                         |
| Weight [g]:   | 276g                           |
| Weight with packaging [g]:                            |                                |
| EAN:  | 5 "904252"615300">             |





The presented photos are for illustration only and may slightly differ from reality. The appearance may depend, among others monitor settings or printing technology. The data presented in this document are not legally binding and are subject to change. The given results were obtained when examining a specific specimen. Elhurt Plus Sp. z o.o. Sp.K, Osieczany 585, 32-400 Myślenice, Poland, edo@edo-solutions.com