

NASTRO LED



EDO777648



ENERGY

EDO
EDO777648

A
B
C
D
E
F
G

12
kWh/1000h

2019/2015

12W/m
1100lm/m
warm white
3000K
12 V DC
120°
IP22
III
5m

LED tape - NASTRO LED COB 12W WW

SPECIFICATIONS EDO777648

Source Type:	LED COB
Application:	indoor
Installation:	tape 3m
Dimensions:	
-length [mm]:	5000mm
-width [mm]:	8mm
-height [mm]:	2mm
-smallest division unit [mm]:	50mm
-cable length [mm]:	150mm
Number of LEDs per meter:	480LED/m
Energy efficiency class [A-G]:	G
Cooperation with a dimmer:	yes
Cover material:	-

TECHNICAL DATA

Power in the on-mode P_{on} [W]:	12W/m
Standby power P_{sb}/P_{net} [W]:	-
Rated voltage [V]:	12VDC
Color of the light:	cold white
Color temperature [K]:	3000K
Color rendering index CRI:	90
Useful luminous flux [lm]:	1100lm/m
Measurement of the luminous flux in:	wide cone (120°)

Light distribution angle [°]:	120°
Rated life [h]:	30000h
Number of cycles on/off:	15000
On-mode energy consumption [kWh/1000h]:	12kWh / 1000h
IP	IP22
Protection class:	III
Mercury content	no
Environmental conditions:	-20...40 °C

LOGISTIC DATA


Collective packaging [pcs.]:	40pcs.
Weight [g]:	110g

EAN:

2 mm



8 mm



*The specifications given are based on a 1m LED strip test.



The presented photos are for illustration only and may slightly differ from reality. The appearance may depend, among others monitor settings or printing technology. The data presented in this document are not legally binding and are subject to change. The given results were obtained when examining a specific specimen. Elhurt Plus S.A., Osieczany 585, 32-400 Myślenice, Poland, edo@edo-solutions.com